

Dräger X-am® 5600 Multi-Gas Detector

Featuring an ergonomic design and innovative infrared sensor technology, the Dräger X-am® 5600 is one of the smallest gas detection instrument for the measurement of up to 6 gases. Ideal for personal monitoring applications, this robust and water-tight detector provides accurate, reliable measurements of flammable and toxic gases and vapors as well as oxygen.



Benefits

Small yet robust

Small, light and easy to use – the robust and water-tight gas detector X-am 5600 is designed for single-handed operation in tough industrial environments. Water- and dustproof according to IP 67 and with an integrated rubber boot, the device provides optimal functionality even under harsh conditions.

Durable infrared technology

Thanks to the high stability and a resistance to contamination, Dräger infrared sensors can generally be used for up to eight years. This advanced technology reduces the cost of ownership considerably because less replacement sensors are needed. In addition, a calibration of the IR sensor is only necessary every 12 months which reduces maintenance costs.

Single or dual sensor – accurate measurement results

The infrared sensor IR Ex allows the measurement of flammable hydrocarbons in the range of the lower explosive limit. The infrared sensor IR CO₂, with a measurement resolution of 0.01 Vol.-%, provides safe and exact measurements as well as a warning against toxic concentrations of carbon dioxide in the ambient air. For those applications where the reliable measurement of flammable substances and CO₂ is specifically needed, the advantages of both can be achieved by a dual sensor (Dual IR CO₂/Ex).

Also in combination with Hydrogen

Besides hydrocarbons, hydrogen can also be a flammable gas. Because sensors based on infrared technology do not warn against hydrogen explosion dangers, the gas detector X-am 5600 combines two sensor signals (Infrared Ex and electrochemical H₂ HC) for reliable hydrogen detection. The X-am 5600 provides the advantages of poison-free technology to be used in areas where, until now, only catalytic Ex sensors have been used.

Various monitoring possibilities

Thanks to the combination of innovative infrared technology and the latest electrochemical Dräger XXS miniature sensors, this 1-to-6 gas detector reliably detects flammable and harmful concentrations of O₂, Cl₂, CO, CO₂, H₂, H₂S, HCN, NH₃, NO, NO₂, PH₃, SO₂, O₃, Amine, Odorant, COCl₂ and organic vapors. With the PC software Dräger CC-Vision, the sensors can easily be exchanged, calibrated or converted to meet the needs of different applications.

Flexible use

An optional external pump which can be operated with hoses up to 45 m in length is the perfect solution for pre-entry measurements in tanks or pipelines. To monitor entire areas, the gas detector X-am 5600 can be used in combination with the innovative air monitor Dräger X-zone 5500.

Benefits


Suitable for Ex-Zone 0

The small and reliable gas detector is suitable for use in areas classified as zone 0, which are areas where explosive atmospheres are always to be expected – also with Dräger X-am® Pump and Dräger X-zone 5500.

Area monitoring

In combination with the Dräger X-zone 5500 the gas detector can be used for various area monitoring applications. Up to 25 Dräger X-zone 5500 units can be automatically interconnected to form a wireless fence. This interconnection of the area monitoring devices allows for the fast securing of larger areas, e.g. pipelines or industrial tanks – even within the scope of industrial shutdowns.

System Components



DrägerSensor XXS

Dräger a conçu des capteurs électrochimiques miniatures spécialement pour le Dräger Pac®, les X-am® 1/2/5 et la génération X-am® 8000. Les capteurs détectent un grand nombre de gaz et de vapeurs. Ils sont aussi très fiables et stables sur le long terme, réduisant ainsi les coûts d'exploitation.

System Components



Dräger Infrared Sensors

Dräger infrared sensors deliver optimal measurement results and are unaffected by sensor poisons. The long service life of these sensors results in hardly any follow-up costs. You can also use Dräger infrared sensors to take Ex and CO₂ measurements simultaneously.



X-dock® 5300/6300/6600 de Dräger

La série Dräger X-dock® vous donne le plein contrôle de vos instruments portatifs de détection de gaz Dräger. Effectués avec une quantité réduite de gaz étalon et des tests de courte durée, les tests au gaz et les étalonnages automatiques permettent un gain de temps et d'argent. La documentation et les évaluations détaillées vous donnent une vue d'ensemble claire.



Station Bump Test de Dräger

Facile à utiliser, autonome et portable. Avec la station Bump Test, les tests fonctionnels de détection de gaz et les dispositifs d'avertissement s'effectuent facilement et rapidement.

Accessories

D-0494-2018



Gaz et accessoires d'étalonnage

L'étalonnage de l'appareil permet à celui-ci de fonctionner en toute sécurité, tout en respectant les règlements et les codes de bonne pratique applicables. Les diverses options d'étalonnage des gaz sont facilement accessibles.

D-30746-2015



Logiciel de configuration et d'évaluation Dräger

Enregistrer les mesures obtenues, configurer de manière professionnelle les instruments de détection de gaz et afficher les données de performance : tout cela est possible avec le logiciel conçu sur mesure par Dräger.

D-11857-2016



Dräger X-am® Pump

The Dräger X-am® Pump is an external pump for the portable gas detectors Dräger X-am® 2500, 5000, and 5600 – designed for clearance measurement, for example in tanks and shafts. The pump automatically switches on when it is connected to a running X-am® device. The change from pump mode to diffusion mode is fast and easy.

D-12284-2009



Power pack & charging set

NiMH supply unit T4 with charger module und power pack

Accessories



ST-14360-2008

Calibration cradle

Related Products



D-14325-2017

Dräger X-am® 5000

The Dräger X-am® 5000 belongs to a generation of gas detectors, developed especially for personal monitoring applications. This 1- to 5-gas detector reliably measures combustible gases and vapors as well as oxygen and harmful concentrations of toxic gases, organic vapors, Odorant and Amine.



D-6491-2017

Dräger X-am® 8000

Clearance measurement was never this easy and convenient: The 1 to 7 gas detector detects toxic and flammable gases as well as vapours and oxygen all at once – either in pump or diffusion mode. Innovative signalling design and handy assistant functions ensure complete safety throughout the process.

Technical Data

Dimensions (W x H x D)	48 x 130 x 44 mm	
Weight	220 – 250 g	
Ambient conditions	Temperature	-20 to +50 °C (-40 to +50 °C for max. 15 minutes)
	Pressure	700 to 1,300 mbar
	Relative humidity	10 to 95 % r.h.
Protection class	IP 67	
Alarms	Visual	360°
	Audible	Multi-tone > 90 dB at 30 cm
	Vibration	
Operating times	~ 12 h	
Charging time	< 4 h	
Datalogger	Can be read out via Infrared > 1,000 hours with 6 gases and a recording interval of 1 value per minute	
Pump operation	Maximum hose length 45 m; 148 ft.	
Approvals	ATEX	I M1 Ex da ia I Ma
		II 1G Ex da ia IIC T4/T3 Ga
	IECEX	IECEX da ia I Ma
		Ex da ia IIC T4/T3 Ga
	CSA (Canada & USA)	Class I Div. 1 Group A, B, C, D, E, F, G T.-Code T4/T3 A/Ex da ia IIC T4/T3 /Ga
	Measurement performance certificate	EN 50104
EN 45544-1, EN 45544-2		CO & H ₂ S
EN 60079-29-1		Methane to nonane, XXS H ₂ HC
CE mark	Electromagnetic Compatibility (Directive 2014/30/EU)	
MED	Marine Equipment Directive (Directive 2014/90/EU)	
EAC	PO Ex ia I Ma X 0Ex ia IIC T4/T3 Ga X	

Ordering Information

Dräger X-am® 5600

83 21 050

Consisting of: basic instrument with an integrated data logger, manufacturer's and calibration certificates. A functional instrument must include up to 4 sensors and a power supply unit (option).

Infrared sensors	Measuring range	Resolution	Order code
Dual IR Ex/CO ₂ ES ¹	0 – 100 % LEL	1 % LEL	68 51 880
	0 – 100 Vol.-% Methane, Propane, Ethene, n-Butane	0.1 Vol.-% CH ₄	
	0 – 5 Vol.-% CO ₂	0.01 Vol.-% CO ₂	
IR Ex ES ¹	0 – 100 % LEL	1 % LEL	68 51 881
	0 – 100 Vol.-% Methane, Propane, Ethene, n-Butane	0.1 Vol.-% CH ₄	
	0 – 5 Vol.-% CO ₂	0.01 Vol.-% CO ₂	
IR CO ₂ ES	0 – 5 Vol.-% CO ₂	0.01 Vol.-% CO ₂	68 51 882
Electrochemical sensors	Measuring range	Resolution	Order code
XXS O ₂ ²	0 – 25 Vol.-%	0.1 Vol.-%	68 10 881
XXS CO LC	0 – 2,000 ppm	1 ppm	68 13 210
XXS O ₂ 100	0 – 100 Vol.-%	0.5 Vol.-%	68 12 385
XXS CO HC	0 – 10,000 ppm	5 ppm	68 12 010

Ordering Information

XXS CO/H ₂ compensated	0 – 2,000 ppm CO	2 ppm	68 11 950
XXS H ₂ S LC ²	0 – 100 ppm	0.1 ppm	68 11 525
XXS H ₂ S HC	0 – 1,000 ppm	2 ppm	68 12 015
XXS CO LC/H ₂ S LC	0 – 2,000 ppm CO 0 – 200 ppm H ₂ S	1 ppm CO 0.1 ppm H ₂ S	68 13 280
XXS CO LC/O ₂	0 – 200 ppm CO 0 – 25 Vol.-% O ₂	1 ppm CO 0.1 Vol.-% O ₂	68 13 275
XXS H ₂ S LC/O ₂	0 – 100 ppm H ₂ S 0 – 25 Vol.-% O ₂	0.1 ppm H ₂ S 0.1 Vol.-% O ₂	68 14 137
XXS NO	0 – 200 ppm	0.1 ppm	68 11 545
XXS NO ₂	0 – 50 ppm	0.1 ppm	68 10 884
XXS NO ₂ LC	0 – 50 ppm	0.02 ppm	68 12 600
XXS SO ₂	0 – 100 ppm	0.1 ppm	68 10 885
XXS PH ₃	0 – 20 ppm	0.01 ppm	68 10 886
XXS PH ₃ HC	0 – 2,000 ppm	1 ppm	68 12 020
XXS HCN	0 – 50 ppm	0.1 ppm	68 10 887
XXS HCN PC	0 – 50 ppm	0.5 ppm	68 13 165
XXS NH ₃	0 – 300 ppm	1 ppm	68 10 888
XXS CO ₂	0 – 5 Vol.-%	0.1 Vol.-%	68 10 889
XXS Cl ₂	0 – 20 ppm	0.05 ppm	68 10 890
XXS H ₂	0 – 2,000 ppm	5 ppm	68 12 370
XXS H ₂ HC	0 – 4 Vol.-%	0.01 Vol.-%	68 12 025
XXS OV	0 – 200 ppm	0.5 ppm	68 11 530
XXS OV-A	0 – 200 ppm	1 ppm	68 11 535
XXS Amine	0 – 100 ppm	1 ppm	68 12 545
XXS Odorant	0 – 40 ppm	0.5 ppm	68 12 535
XXS COCl ₂	0 – 10 ppm	0.01 ppm	68 12 005
XXS Ozone	0 – 10 ppm	0.01 ppm	68 11 540

Electrochemical sensors with 5 years manufacturer's warranty

XXS E CO	0 – 2,000 ppm	2 ppm	15 sec.	68 12 212
XXS E H ₂ S	0 – 200 ppm	1 ppm	15 sec.	68 12 213
XXS E O ₂	0 – 25 Vol.-%	0.1 Vol.-%	10 sec.	68 12 211

ES = Energy saving

HC = High concentration

¹ Special calibrations possible for the Ex sensors (Standard: methane).

² Dräger provides a 3 year manufacturer's warranty on the Dräger X-am® 5000 and these sensors. The legal rights arising from defects remain unaffected.

Power supply units

NiMH power supply T4	83 18 704
Power pack & charging set consisting of: rechargeable NiMH power supply T4, charging module and a single charger (for worldwide use)	83 18 785
Battery holder ABT 0100 (without batteries)	83 22 237
Alkaline batteries T3 (2 pcs.) for battery holder 83 22 237	83 22 239
Alkaline battery T4 (2 pcs.)	83 22 240

Charging accessories

Charging module	83 18 639
-----------------	-----------

Ordering Information

Charging set basic, consisting of one charging module and a single power supply (worldwide use)	83 20 333
Power plug 100–240 VAC; 6.25 A, for charging up to 20 devices Adapter for power plug 83 25 736 is needed in addition.	83 21 850
Single charger (worldwide use) for max. 5 charger modules	83 16 994
Car charging connection cable 12 V / 24 V for a charging module	45 30 057
Vehicle charger mounting kit for one Dräger X-am® 1/2/5x00 charging module	83 18 779
Charging adapter for charging a rechargeable battery without X-am® device	83 26 101
Pump accessories	
Dräger X-am® Pump (external pump)	83 27 100
Dräger X-am® Pump incl. USB charger and shoulder strap	83 27 115
Hand pump adapter	83 19 195
CSE Set Dräger X-am® Pump (incl. 5 m FKM hose)	83 27 117
Case for Dräger X-am® Pump	83 27 104
Calibration accessories	
Calibration cradle	83 18 752
Dräger X-dock® 5300 for Dräger X-am® 1/2/5x00	83 21 880
Dräger Bump Test Station for Dräger X-am® 5600, not including gas cylinder	83 19 131
Dräger Bump Test Station for Dräger X-am® 5600, complete with one test gas cylinder 58L (gas and concentration variable)	83 19 130
Nonane Checker	83 20 080
Communication accessories / software	
Dräger GasVision 7 license key	83 25 646 software: www.draeger.com/software (free trial version)
Dräger CC-Vision	www.draeger.com/software
USB DIRA with USB cable, communication adapter infrared to USB	83 17 409
Area monitoring	
Dräger X-zone® 5500, 868 MHz, 24 Ah battery with diffusion cap	83 24 819
Dräger X-zone® 5500 with integrated pump, 868 MHz, 24 Ah battery with diffusion and pump cap	83 24 821
In conjunction with the portable alarm amplifier Dräger X-zone® 5500 the units are combined to a new system; to monitor whole working areas or to connect to external alarm contacts.	

Notes

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
61 Science Park Road
The Galen #04-01
Singapore 117525
Tel: +65 6872 9288
Fax: +65 6259 0398
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Indústria e Comércio Ltda.
Al. Pucurui - 51 - Tamboré
06406-100 - Barueri - SP
Tel. +55 (11) 4689-4900
relacionamento@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

