



## ARG314 Aerodynamic Rain Gauge



**The cost-effective choice of EML gauge for the professional Hydro-Met Services**

### Applications

- National Met Services
- Hydrology catchment projects
- Hydro-Met stations
- Industrial customers that need accurate data
- Weather enthusiasts
- Flood warning systems

### Features and Benefits

- Optimum Aerodynamic shape from over 10 years of extensive field research
- Self-emptying instrument
- Replaceable reed switch as standard
- 0.1, 0.2 or 0.5mm resolution
- WMO Compliant
- UK manufactured

All EML gauges are rigorously laboratory and field tested. Outdoor field testing is carried out against a WMO compliant pit gauge at multiple sites.



Copyright Environmental Measurements Limited (EML)

7 Jupiter Court  
Orion Business Park  
North Shields  
NE29 7SE  
United Kingdom  
Phone: +44-(0)191-2583757  
email: [sales@emild.net](mailto:sales@emild.net)  
web: [www.emild.net](http://www.emild.net)



The unique design and aerodynamic shape of the ARG314 Tipping Bucket precipitation sensor increases measurement accuracy by capturing more rainfall than traditionally shaped cylindrical gauges. The ARG314 is precision-engineered to minimise out-splash and reduce rainfall losses caused by evaporation. The depth, diameter, and angle of the funnel have all been extensively tested and researched to give the optimum accuracy in the field.



The rugged UV resistant material means that the ARG314 can be installed in extremely hostile conditions. This gauge is available in 0.1mm, 0.2mm or 0.5mm resolution (per tip) and comes as standard with a single contact closure reed switch. A dual reed switch upgrade and/or siphon version are available on request. Quality is assured because the gauge is manufactured and assembled by EML in the UK. The ARG314 is a robust and versatile instrument and is compatible with all modern data loggers and event recorders.

Technical Specifications		Ordering Information	
Resolution	0.1mm, 0.2mm or 0.5mm	Order Code	Product
WMO Compliant	Yes	P-780-300	ARG314/STD (0.1mm) Standard
Output	Contact Closure (Reed Switch) Dual reed switch upgrade available	P-780-301	ARG314/EC (0.1mm) With 6m cable
Typical Accuracy	All gauges 2% up to 25mm/hr (Class A)	P-780-302	ARG314/L (0.1mm) With plug for internal EML logger
	0.1mm Gauge +/- 3% up to 50mm/hr (Class A)	P-780-303	ARG314/STD (0.2mm) Standard
	0.2mm / 0.5mm Gauges +/- 3% up to 120mm/hr (Class A)	P-780-304	ARG314/EC (0.2mm) With 6m cable
Accuracy with Mathematical Correction (0.1mm)	+/- 3% up to 500mm/hr (Class A)	P-780-305	ARG314/L (0.2mm) With plug for internal EML logger
Accuracy with Mathematical Correction (0.2mm)	+/- 3% up to 1000mm/hr (Class A)	P-780-306	ARG314/STD (0.5mm) Standard
Accuracy with Mathematical Correction (0.5mm)	+/- 3% up to 1500mm/hr (Class A)	P-780-307	ARG314/EC (0.5mm) With 6m cable
Operating Temperature	0°C - 70°C	P-780-308	ARG314/L (0.5mm) With plug for internal EML logger
Funnel Diameter	20.0cm / 7.87 Inch	Ordering Information - Accessories	
Funnel Area	314cm <sup>2</sup> / 48.67 sq. Inch	Order Code	Product
Height	43.5cm to 46.5cm (With feet adjustment)	P-780-320	ARG314 Dual reed switch upgrade
Weight	2Kg	P-780-319	ARG314 spares kit
Colour	White	contact sales	ARG314 siphon upgrade

Web: [www.emltd.net](http://www.emltd.net)

e-mail: [sales@emltd.net](mailto:sales@emltd.net)



Copyright Environmental Measurements Limited (EML)

7 Jupiter Court  
Orion Business Park  
North Shields  
NE29 7SE  
United Kingdom  
Phone: +44-(0)191-2583757  
email: [sales@emltd.net](mailto:sales@emltd.net)  
web: [www.emltd.net](http://www.emltd.net)